CANENCEPEEN DIGITAL SIGNAGE SOLUTION

QBIC TD-1070 ULTRA SLIM

- fanless 10" Touch Panel PC
- Android 11 / SMIL / HTML5
- slim housing (21 mm)
- LED indicator shows immediately if the room is available (True Color)
- PoE+ (power over ethernet)
- RTSP (real time streaming protocol)
- available in black
- 2 years warranty
- article number: TD-1070-B

BAS OSCIPEEN Digital signage solution	
H2.301	10:00
Board meeting	
	Cancel
Duration: 10:00 - 15:00	+ -
	Menu

TECHNICAL SPECIFICATION

Features	
Programming API	HTML5 / SMIL / Android API
CPU	ARM quad-core 2 GHz
RAM	2 GB LPDDR4
Storage	32 GB eMMC
Orientation	Landscape / Portrait format
Video Decoder	H.264 / H.265, VC-1 / MPEG-4 / VP9
Image codecs	JPEG/ BMP / GIF / PNG
Audio	MPEG / OGG / AAC
Status LED	True Color LED

IO Interface	
Ethernet	1 x RJ45 (10/ 100 Mbps), PoE+
Power supply	optional: power supply DC 25 Volt *
WLAN	optional: 802.11 b/g/n/ac *
USB	2 x USB 2.0, 1 x USB 3.0
Analog Stereo out	1 x 3,5 mm jack plug
Memory expansion	1 x Micro SDHC slot

The data sheet is subject to change, liability for errors and mistakes is excluded.

Display	
Size	10.1"
Resolution	1920 x 1200 px
Brightness	430 nits
Contrast ratio	1000:1
Dimensions	242.9 x 173.4 x 20.5 mm
Weight	581 g
Certification	CE, FCC, BSMI, NCC, IMDA, RoHS

* Not included in the scope of delivery.

Requirements	
easescreen	eSign Server, HTML5 eSign Client

AREAS OF APPLICATION

- conference- and meeting rooms in companies
- congress centres
- universities and schools
- hotels
- public buildings
- authorities and agencies

DATASHEET QBIC TD-1070 ULTRA SLIM

QBIC TD-1060 SLIM

- fanless 10" Touch Panel PC
- Android 8.1 / SMIL / HTML5
- slim housing (21 mm)
- LED indicator shows immediately if the room is available (True Color)
- PoE+ (power over ethernet)
- RTSP (real time streaming protocol)
- available in black
- 2 years warranty
- article number: TD-1060SLIM-B



TECHNICAL SPECIFICATION

Features	
Programming API	HTML5 / SMIL / Android API
CPU	ARM quad-core 1.5 GHz
RAM	2 GB DDR3L
Storage	16 GB eMMC
Orientation	Landscape / Portrait format
Video Decoder	H.264 / H.265, VC-1 / MPEG-4 / VP8
Image codecs	JPEG/ BMP / GIF / PNG
Audio	MPEG / OGG / ACC
Status LED	True Color LED

IO Interface	
Ethernet	1 x RJ45 (10/ 100 Mbps), PoE+
Power supply	optional: power supply DC 12 Volt *
WLAN	optional: 802.11 b/g/n/ac *
USB	2 x USB 2.0
Analog Stereo out	1 x 3.5 mm jack plug
Memory expansion	1 x Micro SDHC slot

The data sheet is subject to change, liability for errors and mistakes is excluded.

Display	
Size	10.1"
Resolution	1280 x 800 px
Brightness	350 nits
Contrast ratio	1000:1
Dimensions	248 x 166 x 20.8 mm
Weight	615 g
Certification	CE, FCC, BSMI, NCC, IMDA, RoHS
Optional *	adjustable stand (30°, 45° oder 60°) (o.r.)

* Not included in the scope of delivery.

Requirements	
easescreen	eSign Server, HTML5 eSign Client

AREAS OF APPLICATION

- conference- and meeting rooms in companies
- congress centres
- universities and schools
- hotels
- public buildings
- authorities and agencies

DATASHEET QBIC TD-1060 SLIM

QBIC TD-1050 PRO

- fanless 10" Touch Panel PC
- Android 8.1/10
- slim housing (27mm)
- NFC (Near Field Communication)
- LED indicator shows immediately if the room is available (True Color)
- PoE+ (power over ethernet)
- RTSP (real time streaming protocol)
- available in black
- 2 years warranty
- article number: TD-1050PRO



TECHNICAL SPECIFICATION

Features	
Programming API	HTML5/ SMIL/ Android SDK
CPU	ARM octa-core 1.5 GHz
RAM	2 GB DDR3
Storage	16 GB eMMC
Orientation	Landscape format
Video decoder	H.264/ MPEG-4/ VC-1/ MVC
Image codecs	JPEG/ PNG (max. 1920 x 1080)
Audio	MP3
Status LED	True Color LED (24 bit)
NFC	ja
Camera	1x 8M AF F2.0

IO Interface	
Ethernet	1x RJ45 (10/100 Mbps), PoE+
Power supply	optional: power supply DC 12 Volt
WLAN	802.11 b/g/n
USB	2 x USB 2.0
Analog Stereo out	1 x 3.5 mm jack plug
Memory expansion	1x Micro SDHC slot

The data sheet is subject to change, liability for errors and mistakes is excluded.

Display	
Size	10.1"
Resolution	1280 x 800 px
Brightness	300 nits
Contrast ratio	1000:1
Dimensions	261.1 x 193.3 x 27 mm
Weight	710 g
Certification	CE, FCC, RoHS
Optional *	Housing for flush mounting (p.o.r.)

* Not included in the scope of delivery.

Requirements		
easescreen	eSign Server, HTML5 eSign Client	

AREAS OF APPLICATION

- conference- and meeting rooms in companies
- congress centres
- universities and schools
- hotels
- public buildings
- authorities and agencies

DATASHEET QBIC TD-1050 PRO

CANENCIPEEN DIGITAL SIGNAGE SOLUTION

ELO I-Series, 21.5"

- digital doorsign with integrated touch sensoric
- Android 7.1
- size: 21.5"
- available in black or white
- provides WLAN, Ethernet and Bluetooth
- article number: ES-E22-B (black), ES-E22-W (white)



TECHNICAL SPECIFICATION

Features	
Operating System	Android 7.1
CPU	APQ8053 2.0-GHz Octa-Core Processor
RAM	3 GB DDR3L
Storage	32 GB SSD
Ports	Bluetooth 4.1, 1x LAN (Gigabit), 1x USB 3.0 support
Power supply	via power supply (100-240 VAC, 50-60Hz)
Dimensions	323.9 x 523.9 x 35.2 mm
Size	21.5"
Resolution	Full HD 1920 x 1080 px
Brightness	250 nits
WLAN	802.11 b/g/n/ac

Requirements	equirements	
easescreen	eSign Server, HTML5 eSign Client	

The data sheet is subject to change, liability for errors and mistakes is excluded.

AREAS OF APPLICATION

- conference- and meeting rooms in companies
- room booking
- ressource management
- congress centres
- universities and schools
- hotels
- public buildings
- authorities and agencies

DATASHEET ELO I-SERIES, 21.5"

ELO I-Series, 15.6"

- digital doorsign with integrated touch sensoric
- Android 7.1
- size: 15.6"
- available in black or white
- provides WLAN, Ethernet and Bluetooth
- article number: ES-E15-B (black), ES-E15-W (white)



TECHNICAL SPECIFICATION

Features	tures	
Operating System	Android 7.1	
CPU	APQ8053 2.0-GHz Octa-Core Processor	
RAM	3 GB DDR3L	
Storage	32 GB SSD	
Ports	Bluetooth 4.1, 1x LAN (Gigabit), 1x USB 3.0 support,4x microUSB	
Power supply	via power supply (100-240 VAC, 50-60Hz)	
Dimensions	386.74 x 248.17 x 28.3 mm	
Size	15.6"	
Resolution	Full HD 1920 x 1080 px	
Brightness	300 nits	
WLAN	802.11 b/g/n/ac	

Requirements	uirements	
easescreen	eSign Server, HTML5 eSign Client	

The data sheet is subject to change, liability for errors and mistakes is excluded.

AREAS OF APPLICATION

- conference- and meeting rooms in companies
- room booking
- ressource management
- congress centres
- universities and schools
- hotels
- public buildings
- authorities and agencies

